

IRONERS

TFI 6026 · 6032



STANDARD FEATURES & BENEFITS

- Ergonomic cylinder heated ironer
- Gas or electric heating
- Extended heat transfer path
- Large surface contact with linen
- Roll standard with chrome surface coating for better thermal conduction and highly resistant to corrosion, even after periods of inactivity
- Finger protection panel and emergency button for more safety
- Easy to use electronic control with pre-set ironing programmes
- Indication of ironing temperature and speed
- Frequency controlled motor
- Reverse mode possible
- Space-saving wall model with front return of the linen
- Overheating check system with 2 temperature sensors
- Premix burner for more power and efficient ironing
- LED lights on the ironing width for good visibility and operation

OPTIONS

- Longitudinal fold
- 3 folding sensors at feeding point instead of 1
- Transport wheels
- Rear output of the linen

TOLON

IRONERS

TFI 6026 · 6032

MODEL	UNIT	TFI 6026	TFI 6032
Roll diameter	mm	600	600
Working width	mm	2600	3200
Roll speed	m/min	3,5-12	3,5-12
Performance* Electric folding	kg/h	145-162	180-200
HEATING			
Electric			
Electric heating power **	kW	56	69
Evaporation	l/h	65	80
Electric consumption	kW/h	57,8	71
Gas			
Gas heating power	kW	65	80
	Btu	221789	272971
Evaporation	l/h	80	100
Gas connection Ø	DN/BSP	20 (¾")	20 (¾")
Gas pressure	mbar	20-60	20-60
Gas consumption	kW/h	56	84
	Btu/h	190350	287320
VOLTAGE/ELECTRIC CONNECTION			
Electric			
		380-415V 3ph + N 50Hz	
		380-415V 3ph + N 60Hz	
		440-480V 3ph 50Hz	
		440-480V 3ph 60Hz	
Gas			
		380-415V 3ph + N 50Hz	
		380-415V 3ph + N 60Hz	
		440-480V 3ph 50Hz	
		440-480V 3ph 60Hz	
		200-240V 3ph 50Hz	
		200-240V 3ph 60Hz	
		200-240V 1ph 50/60Hz	
MOTORS			
Roll motor	kW	0,75	0,75
Fan motor	kW	1,1	1,1
EXHAUST			
Exhaust connection Ø	mm	125	125
Airflow			
Electric	m³/h	1125	1125
Gas	m³/h	1125	1125
DIMENSIONS (WxDxH)			
Standard	mm	3552 x 1351 x 1598	4152 x 1351 x 1598
Standard rear exit model	mm	3552 x 1647 x 1598	4152 x 1647 x 1598
Packed	mm	3650 x 1500 x 1758	4250 x 1500 x 1758
Packed rear exit model	mm	3650 x 1800 x 1758	4250 x 1800 x 1758
WEIGHT			
Net	kg	1825	2010
Gross	kg	1975	2220
SOUND LEVEL			
	db(A)	< 65,6	< 65,6

* 50% moisture - folding at 9 m/min

** Output calculated at 380V/IIIphase

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

www.tolon.com

TOLON